



リード端子の組成はSN-CU(CP-TC) 又は SN(CP-T)

③	メッキ	鉛フリー	CP-T	T	(2.65)
②	端子	10P		U	(5.50)
①	ボビン	1P			
BOBBIN	材質	フェノール樹脂	PM9750	V	(2.50)
端子	CP線	電気メッキ	φ0.6	Z	(13.00)
品名	BE16-1110CPNFR			φX	(0.60)
白石工業(株)		2014/1/27		Y	(0.80)

記号	寸法	記号	寸法
R1	(0.20)	A1	(13.00)
R2	(0.30)	A2	11.35 ^{+0.10} -0.10
R3	(0.50)	B1	(6.35)
R4	(1.00)	B2	(5.65)
		C1	5.15 ^{+0.10} -0.10
		C2	4.45 ^{+0.10} -0.10
		D	9.75 ^{+0.10} -0.10
		E1	(0.80)
		E2	(1.50)
		F	(0.80)
		G	(1.70)
		H	(8.20)
		I	(1.70)
		K	(16.00)
		N1	(2.60)
		N2	(2.00)
		P1	(10.50)
		P2	(3.25)
		S1	(5.15)
		T	(2.65)
		U	(5.50)
		V	(2.50)
		Z	(13.00)
		φX	(0.60)
		Y	(0.80)